



AP-1200 EPDM RINSEABLE PRIMER

PRODUCT DESCRIPTION

ARMOUR PROOF AP-1200 is a low viscosity, water-based rinseable cleaner. It is designed to chemically alter the surface of new and weathered EPDM membranes by breaking down the chemical bond of the inorganics on the surface and increasing the adhesion of the ARMOUR PROOF AP-3100, AP-3200 and AP-3300 roof coatings to the substrate.

SURFACE PREPARATION AND APPLICATION

Remove all visible dirt and debris by broom or air blower prior to application. Apply AP-1200 with a 2-3 gallon pressure sprayer at a rate of 300-400 square feet per gallon. Allow the material to stand for 15-20 minutes to wet out and react with the EPDM surface. High-pressure rinse the surface with a minimum of 2,000 psi washer, keeping the tip within 12" of the surface. Use a squeegee to push the excess water towards the drains. After the roof is cleaned, the surface will be jet black in appearance. If it appears dull and weathered, the process must be repeated. Surface must be dry before the coating application. EPDM Substrate must be coated within 5 days of this application. Refer to the Armour Proof Coatings Specification for detailed instructions on how to prepare the specific substrate.

LIMITATIONS AND PRECAUTIONS

Do not apply AP-1200 when ambient air and substrate temperatures fall below 50° F, or if inclement weather is forecasted. Do not apply if ambient temperature will drop below 32° F or dew will settle before coating is allowed to dry. Do not store sealed containers in prolonged sunlight. Wear rubber gloves and eye protection when working with AP-1200. PROTECT FROM FREEZING DURING SHIPMENT AND STORAGE. Do not store material at temperatures below 45° F. It will freeze and become unusable at temperatures below 32° F.

WARRANTY

This product will perform as claimed if directions are followed. Armour Proof Coatings cannot control conditions of application and substrate, or methods used. This warranty is limited to replacement or refund value of the defective material used, and does not include labor or labor costs

Tools needed



Technical Data

SOLUBILITY IN WATER:
100% Soluble

PH:
11

VOC CONTENT:
0 lb/gal (0 g/l)

SHELF LIFE:
12 months @ 40° -90° F

SET TIME TO RINSE:
10-15 minutes

COLOR:
Clear

Available in the following sizes:

