

Revision Date: 03.19.20

Del-Val

DELIVERING VALUE

DEL-VAL 112 BLACK SEAL RUBBERIZED ROOF COATING

Description

Del-Val 112 Black Seal Rubberized Roof Coating contains a blend of SBS rubbers with solvent based asphalts and reinforcing fibers which forms an elastomeric coating. Del-Val 112 Black Seal dries to a tough, durable, flexible coating that gives excellent performance over a wide range of temperatures and weather conditions.

Uses

Del-Val 112 Black Seal is designed for a use of flat roof surfaces with positive drainage. It may be used on a variety of surfaces including new or existing built up roofs, APP, SBS, smooth or granulated surfaces, metal surfaces and roll-roofing. **DO NOT USE with TPO, EPDM, PVC or other single ply membranes.**

Preparation

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Repair all holes, cracks, blisters, tears or breaks by spreading Roof Master Plus over damaged area then embed United Asphalt Cotton or Fiberglass fabric. Must mechanically mix coating before using.

Application

Apply to a clean dry surface using a brush, roller or squeegee. For best results weather should be clear with no threat of rain for 48 hours.

Coverage

Metal Surfaces: Apply at the rate of approximately 1 gallon per 100 sq. ft.

Roofing Surfaces (Asphalt Surfaces): Apply at the rate of approximately 2 gallons per 100 sq. ft.

Cleanup

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.


Code Approvals/Compliance

This product meets or exceeds the requirements of ASTM D-4479 Type I

LEARN MORE  UnitedAsphalt.com/DV112



TOOLS NEEDED



PACKAGING SIZES

