

Revision Date: 03.19.20

# Del-Val

DELIVERING VALUE

## DEL-VAL 121 NON-FIBERED EMULSION COATING

### Description

Del-Val 121 Non-Fibered Emulsion Coating is an asphalt based clay emulsion coating designed for both brush and spray applications on a variety of roof surfaces. This product has excellent resistance to water and cures to a tough durable finish.

### Uses

Del-Val 121 Non-Fibered Emulsion Coating may be used on smooth surfaces BUR, SBS, APP bituminous membranes, metal surfaces, and roll-roofing. It can also be used for damp-proofing above and below-grade foundation walls and other masonry surfaces.

### Preparation

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Repair all holes, cracks, blisters, tears or breaks by spreading Del-Val 211 Flashing Cement over damaged area then embed United Asphalt Cotton or Fiberglass Fabric.

### Application

Apply to a clean surface using a brush, squeegee, or spray equipment. For best results weather should be clear with no threat of rain for 48 hours.

### Coverage

Apply at the rate of approximately 3 gallons per 100 sq. ft. Must stir coating before using.

### Cleanup

Clean tools with warm water and soap.


### Code Approvals/Compliance

This product meets or exceeds the requirements of ASTM D 1227-87 Type III

**LEARN MORE**  [UnitedAsphalt.com/DV121](http://UnitedAsphalt.com/DV121)



### TOOLS NEEDED



### PACKAGING SIZES

