

Revision Date: 03.19.20



DEL-VAL 210 PLASTIC CEMENT

Description

Del-Val 210 Plastic Cement is formulated to a heavy smooth trowel consistency. This product is used as a cold applied plastic cement for asphalt roof membranes. Del-Val 210 Plastic Cement is ideal for plastic details and a variety of waterproofing repairs such as roof penetrations and moving joints.

Uses

Del-Val 210 is specially formulated for vertical surfaces. This product is primarily used for repairing, asphalt shingles, built-up roofs, metal and masonry surfaces. Great for sealing leaks and openings at flashings (chimneys, vents, skylights, metal joints, gutters). Damp-proofing of concrete, masonry walls and foundations. **DO NOT USE with EPDM, PVC, TPO or other single-ply membranes.**

Preparation

Surface must be clean and free of dirt, dust, oil or grease and be free of any other foreign matter that would interfere with good adhesion. In colder climates we recommend storing the product at room temperature for 24 hours prior to application.

Application

Apply with a trowel or putty knife. Spread Del-Val 210 Plastic Cement to approximately 1/8" thickness and work thoroughly into the problem area. Repairing cracks and blisters: if the area is 1/4" wide to 2" long apply United Asphalt Cotton or Fiberglass Fabric for reinforcement then cover with additional cement.

Coverage

Approximately 8 gallons per 100 sq. ft.

Code Approvals/Compliance

Federal Specification SS-C-153 Type I (Except Non-Asbestos). This product meets or exceeds the requirements of ASTM 4586 Type I

Cleanup


Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.

Precaution

DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F.



TOOLS NEEDED ✓



PACKAGING SIZES ✓



LEARN MORE  UnitedAsphalt.com/DV210