

Revision Date: 03.19.20

# Del-Val

DELIVERING VALUE

## DEL-VAL 213 ELASTOMERIC SEALANT - TROWEL GRADE

### Description

Del-Val 213 Elastomeric Sealant (Trowel Grade) contains a blend of SBS rubbers with solvent based asphalts and reinforcing fibers. Del-Val 213 Elastomeric Sealant (Trowel Grade) dries to a tough, durable, flexible coating that gives excellent performance over a wide range of temperatures and weather conditions.

### Uses

Del-Val 213 (Trowel Grade) is designed for the use on flat & vertical roof surfaces to repair seams, penetrations and any area of need. It may be used on a variety of surfaces including new or existing built up roofs, APP, SBS, smooth or granulated surfaces, metal surfaces and roll-roofing. **DO NOT USE with TPO, EPDM, PVC or other single-ply membranes.**

### Preparation

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Repair all holes, cracks, blisters, tears or breaks by spreading Del-Val 213 (Trowel Grade) over damaged area then embed United Asphalt Cotton, Fiberglass or Polyester Fabric. **Must mechanically mix coating before using.**

### Application

Apply to a clean dry surface using a trowel. For best results weather should be clear with no threat of rain for 48 hours.

### Coverage

**Metal Surfaces:** Apply at the rate of approximately 1 gallon per 80 linear feet.


**Asphalt Surfaces:** Apply at the rate of approximately 1 gallons per 80 linear feet.

### Cleanup

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.



### TOOLS NEEDED ▾



### PACKAGING SIZES ▾



**LEARN MORE** → [UnitedAsphalt.com/DV213TG](http://UnitedAsphalt.com/DV213TG)