

Revision Date: 03.19.20

Del-Val

DELIVERING VALUE

DEL-VAL 232 MODIFIED ALUMINUM MASTIC

Description

Del-Val 232 Modified Aluminum Mastic is a premium, reflective elastomeric mastic formulated to a heavy smooth trowel consistency with great elasticity. It is a single component, SBS polymer modified asphalt blended with aluminum pigment and specialty fibers. The elastic properties provide great strength and elongation.

Uses

Del-Val 232 Modified Aluminum Mastic is used as flashing cement in any type of asphalt roof membranes where aluminum coating is present. Del-Val 232 is ideal for roof repair, attaching roofing membranes, and parapet walls. **Do Not Use with EPDM, PVC, TPO or other single-ply membranes.**

Preparation

Surface must be clean and free of dirt, dust, oil or grease and be free of any other foreign matter that would interfere with good adhesion. In colder climates we recommend storing the product at room temperature for 24 hours prior to application. Do not apply in ponding water or when water is present.

Application

Apply with a trowel or putty knife. Spread Del-Val 232 to approximately 1/8" thickness and work thoroughly into the problem area. Repairing cracks and blisters: if the area is 1/4" wide to 2" long, apply United Asphalt Cotton or Fiberglass Fabric for reinforcement then cover with additional cement.

Coverage

Approximately 8 gallons per 100 sq. ft. (per coat)

Cleanup

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.


Precaution

DO NOT THIN. DO NOT HEAT CONTAINER. Do not store in an area where temperatures exceed 120°F.

LEARN MORE → UnitedAsphalt.com/DV232



TOOLS NEEDED ✓



PACKAGING SIZES ✓

