

Revision Date: 01.07.20



CANT & TAPERED EDGE

WOOD FIBERED SPECIFICATIONS

Conforms to ASTM C 208

Features/Benefits

- ▶ Dimensionally stable
- ▶ Environmentally friendly, 100% recyclable
- ▶ May contribute to LEED credits
- ▶ Cuts with a knife

May help contribute to LEED credits:

- ▶ **MR Credit 4:** Recycled Content
- ▶ **MR Credit 5:** Regional Materials
- ▶ **MR Credit 6:** Rapidly Renewable Materials
- ▶ **IEQ Credit 4.4:** Low-Emitting Materials – Composite Wood and Agrifiber Products

PERLITE SPECIFICATIONS

Conforms to ASTM Standard C728 n UL Flame Spread Rating 25

Features/Benefits

- ▶ 25% post-consumer recycled content and comply with the Environmental Protection Agency Regulation 40 CFR Part 248

May help contribute to LEED credits:

- ▶ **MR Credit 4:** Recycled Content
- ▶ **MR Credit 5:** Regional Materials

ROCKWOOL SPECIFICATIONS

Conforms to ASTM Standard C 726, ASTM E 84 (UL723), ASTM C 209, ASTM E 96, ASTM C 518 (C 177), ASTM C 665, ASTM C 795, ASTM C 165, ASTM C 612-09



Features/Benefits

- ▶ Will not promote blistering
- ▶ Does not gas off
- ▶ High impact resistance
- ▶ Dimensionally stable
- ▶ Low moisture sorption
- ▶ Non-corrosive
- ▶ Fire resistant
- ▶ Made from natural & recycled materials

*Due to manufactures specifications insulation panels can vary +/- 1/8" in thickness and subtract 1/8" during the tapering process.