

Revision Date: 12.10.21

Del-Val

DELIVERING VALUE

DEL-VAL 400 NON-FIBERED FOUNDATION COATING

Description

Del-Val 400 Non-Fibered Foundation Coating is a non-fibrated asphalt coating that is used to prevent moisture penetration through foundation wall surfaces. After the product is applied it forms a smooth, flexible shell that helps resist the entrance of moisture through foundation walls.

Uses

Del-Val 400 Non-Fibered Foundation Coating is used for exterior below-grade masonry and block walls where no hydrostatic pressure is present.

Preparation

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Must stir coating before using.

Application

Can be applied using: brush, roller, or heavy duty spray equipment. Allow 24 hours drying time before backfilling against the foundation walls. Do not apply over wet/damp or frost covered surfaces.

Coverage

Masonry Surfaces: apply at the rate of approximately 1 to 1.5 gallons per 100 sq. ft.

Cleanup

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.

Precaution

DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F


Code Approvals/Compliance

This product meets or exceeds the requirements of ASTM D449-83 Type I & ASTM D-4479 Type I

LEARN MORE  UnitedAsphalt.com/DV400



TOOLS NEEDED



PACKAGING SIZES

