

ARMOUR PROOF COATINGS

Revised: 03.01.23

AP-2300 Acrylic Mastic

PRODUCT DESCRIPTION

Armour Proof AP-2300 Acrylic Mastic is an acrylic, heavy bodied elastomeric mastic. It offers good elongation and tensile strength properties, resisting lateral movement and allowing for expansion and contraction. Armour Proof **AP-2300 Acrylic Mastic** is used for many different applications, including cracks, seams, fasteners and penetrations.

TECHNICAL DATA

TOTAL SOLIDS BY WEIGHT:	73.7% ± 2
TOTAL SOLIDS BY VOLUME:	63.7% ± 2
WEIGHT PER GALLON:	11.26 lbs. per gallon
VOC CONTENT:	2.94 lbs. per gallon
LOW TEMPERATURE FLEXIBILITY:	Passes
SERVICE TEMPERATURE:	-40° to 200° F
CLEAN UP:	Soap and Water
SHELF LIFE:	12 months @ 40° - 90° F
COLOR:	White ○
PACKAGING:	1, 3.5 and 5-Gallon Pail

APPLICATION

Apply AP-2300 by brush or trowel. When necessary, embed **AP-8100 Series Polyester** reinforcement into the wet product and smooth out free of all wrinkles and fishmouths. Roof coating may be applied after 2-6 hours of application.

PREPARATION OF SUBSTRATE

Surface must be pressure washed clean, free of all loose particles, dirt debris and other contaminants that could inhibit adhesion. Refer to the Armour Proof Coatings Specification for detailed instructions on how to prepare the specific substrate.

LIMITATIONS AND PRECAUTIONS

AP-2300 is a water-based, elastomeric, acrylic coating and is not freeze-thaw stable. Do not apply **AP-2300** when ambient air and substrate temperatures fall below 50° F, or if inclement weather is forecasted. Do not apply over wet substrates or in inclement weather. Do not apply if ambient temperature will drop below 32° F in a 24-hour period or dew will settle before coating is allowed to dry. Do not store sealed containers in prolonged sunlight. **PROTECT FROM FREEZING DURING SHIPMENT AND STORAGE.** Do not store material at temperatures below 45° F. It will freeze and may become unusable at temperatures below 32° F.


WARRANTY

This product will perform as claimed if directions are followed. Armour Proof Coatings cannot control conditions of application and substrate, or methods used. This warranty is limited to replacement of the defective material used, and does not include labor or labor costs.

LEARN MORE → UnitedAsphalt.com/AP2300



TOOLS NEEDED ▾



PACKAGING SIZES ▾

