

Revision Date: 03.01.23

Del-Val

DELIVERING VALUE

DEL-VAL 101 SINGLE-PLY ETCHING PRIMER

DESCRIPTION

Del-Val 101 Single-Ply Etching Primer is a solvent-based primer designed to maximize adhesion to surfaces that can be difficult to adhere to, such as TPO, PVC, Hypalon and a variety of other substrates. It is a fast-drying primer that provides strong adhesion on weathered and un-weathered surfaces. Del-Val 101 is intended for use over a cleaned roof surface; contaminants such as dirt and debris prevent proper adhesion.

USES

Del-Val 101 Single-Ply Etching Primer lays an excellent foundation surface for roof coatings. For example, restoring a roof with our Del-Val 320 Silicone Roof Coating.

PREPARATION

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter.

APPLICATION

Apply Del-Val 101 until roof appears to be a consistent charcoal color. Apply primer with small airless sprayer or a medium nap roller. Over-application or use of multiple coats can reduce adhesion performance. Del-Val 101 should be top coated within 7 days.

COVERAGE

Apply at a rate of 330 square feet per gallon (0.33 gallons per square). Additional material may be required for porous substrates. Must stir before using.


CLEANUP

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.

LEARN MORE  [UnitedAsphalt.com/DV101](https://www.unitedasphalt.com/DV101)



TOOLS NEEDED



PACKAGING SIZES

