

Revision Date: 03.01.23

Del-Val

DELIVERING VALUE

DEL-VAL 205 CAP MASTIC

DESCRIPTION

Del-Val 205 Cap Mastic is manufactured by blending asphalts and mineral fillers and refined solvents. The fillers in this product strengthen the liquid asphalt to form a tough but elastic surface. Once cured, it will stay flexible and not crack in the cold and hot climates. This enables the product to set quickly with less slippage of field sheets. Del-Val 205 is formulated to a heavy duty brush consistency providing a secure bed in which to lay sheet goods.

USES

Used in the application of 90 lb. roll roofing paper or SIS Felt as a cold process adhesive. It can also be used, with polyester mat as an inter-ply cold process adhesive in the creation of a BUR system. It can also be used over aged BUR roofs as a flood coat prior to the introduction of aggregate or other protective coating. **DO NOT USE with EPDM, PVC, TPO or other single-ply membranes.**

PREPARATION

Surface must be clean and free of dirt, dust, oil or grease and be free of any other foreign matter that would interfere with good adhesion. In colder climates we recommend storing the product at room temperature for 24 hours prior to application.

APPLICATION

Apply to a clean dry surface with a brush, roller or squeegee.

COVERAGE

Apply at a rate of 2 to 3 gallons per 100 sq. ft.

CLEANUP

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.

PRECAUTION

DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F.

CODE APPROVALS/COMPLIANCE


This product meets or exceeds the requirements of ASTM D-3019 Type III

V.O.C. Less than 200 g/L

LEARN MORE  UnitedAsphalt.com/DV205



TOOLS NEEDED



PACKAGING SIZES

