

Revision Date: 03.01.23

Del-Val

DELIVERING VALUE

DEL-VAL 211 FLASHING CEMENT

DESCRIPTION

Del-Val 211 Flashing Cement is a high quality cement that is formulated to a heavy smooth trowel consistency. This product is used as a cold applied flashing cement in many types of asphalt roof membranes. Del-Val 211 Flashing Cement is ideal for flashing details and a variety of waterproofing repairs such as roof penetrations and moving joints.

USES

Specially formulated for vertical surfaces. This product is primary used for repairing flashings, asphalt shingles, built-up roofs, metal and masonry surfaces. Great for sealing leaks and openings at flashings (chimneys, vents, skylights, metal joints, gutters). Damp-proofing of concrete, masonry walls and foundations. **DO NOT USE with EPDM, PVC, TPO or other single-ply membranes.**

PREPARATION

Surface must be clean and free of dirt, dust, oil or grease and be free of any other foreign matter that would interfere with good adhesion. In colder climates we recommend storing the product at room temperature for 24 hours prior to application.

APPLICATION

Apply with a trowel or putty knife. Spread Del-Val 211 Flashing Cement to approximately 1/8" thickness and work thoroughly into the problem area. Repairing cracks and blisters: if the area is 1/4" wide to 2" long, apply United Asphalt Cotton or Fiberglass Fabric for reinforcement then cover with additional cement.

COVERAGE

Approximately 8 gallons per sq (per coat)

CLEANUP

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.


CODE APPROVALS/COMPLIANCE

This product meets or exceeds the requirements of ASTM 4586 Type I

LEARN MORE  UnitedAsphalt.com/DV211



TOOLS NEEDED



PACKAGING SIZES

