

Revision Date: 03.01.23

# Del-Val

DELIVERING VALUE

## SS-1H TACK COAT

### DESCRIPTION

Del-Val 505 SS-1h Tack Coat is an anionic emulsion asphalt binder used foundationally in the paving industry for patching, tack coating, fog seal, dust control and other specialty applications. Del-Val 505 SS-1h Tack Coat is a formulation of water, asphalt, emulsifiers and surfactants and promotes adhesion to blacktop surfaces.

### USES

Del-Val 505 SS-1h Tack Coat is used for all paving uses and should be applied at a higher temperature to promote the best curing results.

### APPLICATION

Apply Del-Val 505 SS-1h Tack Coat using a brush, squeegee, or heavy duty spray equipment. Once dry, apply finish coat material over Del-Val 505 SS-1h Tack Coat. Its lower penetration, when compared to SS-1 with a softer base, makes it ideal for warmer climates and should only be applied when temperatures are expected to remain above 55°F for the next 24 hours. For best results, the weather should be clear with no threat of rain for 48 hours at the time of application.

### COVERAGE

Approximately 100 sq. ft./gal.

### PRECAUTION

Avoid contaminants and over-exposure to air and foreign chemicals. Keep from overheating maintaining a storage and application temperature between 55°F and 130°F.


### CODE APPROVALS/COMPLIANCE

Del-Val 505 SS-1h Tack Coat meets the following specifications when tested in accordance with ASTM D977.

**LEARN MORE** → [UnitedAsphalt.com/DV505](https://www.unitedasphalt.com/DV505)



### TOOLS NEEDED ✓



### PACKAGING SIZES ✓

