

Revision Date: 08.20.25



DEL-VAL 242 HYBRID LIQUID SEALANT (WHITE & BLACK)

KEY FEATURES

- Versatile Application
- Ultra-Low VOC
- Broad Use Cases
- Remains Flexible
- Low Dirt Pickup
- Apply at 40°F – 100°F

SUBSTRATE COMPATIBILITY

- Aluminum
- Asphalt (BUR & SBS)
- Coated Metal
- EPS Foam
- Single-Ply (EPDM, Primed TPO, Hypalon, PVC)
- Stainless Steel (HVAC Units)

DESCRIPTION

Del-Val 242 Hybrid Liquid Sealant is a silicone/urethane hybrid sealant used by professionals to produce a water-resistant seal on roof repairs and pitch pan filler. Del-Val 242 Hybrid Liquid Sealant delivers excellent elongation and remains flexible after curing. This semi-self-leveling, single component sealant may be applied to penetrations, seams, curbs, flashings and pitch pans on a wide range of surfaces. Plus its low VOC/eco-friendly chemistry makes it safer and better for the environment.

PREPARATION

Clean surface to be coated. Sweep off all loose dirt, dust and debris. Scrub grease and oil spots with an all-purpose detergent. A primer is not required but may help aid in adhesion.

APPLICATION

Remove all dirt, oil, loose paint, frost and other contamination from all working surfaces. To ensure ease in application, keep at room temperature prior to usage. Test and evaluate to ensure adequate adhesion.

CLEANUP

Clean tools with Del-Val Orange Cleaner & Degreaser or mineral spirits, taking necessary precautions when handling combustible liquids.

SHELF-LIFE AND STORAGE


The shelf life is 12 months for an unopened container from date of manufacture. Refer to the date of manufacture in the format YYMMDD. eg. 250724 was manufactured June 24, 2025.

Refer to SDS for more information.

LEARN MORE ➞ [UnitedAsphalt.com/DV242](https://www.UnitedAsphalt.com/DV242)



TOOLS NEEDED ▼



PACKAGING SIZES ▼



SCAN HERE ➞



DEPEND ON
Del-Val
DELIVERING VALUE