



A United Asphalt Company Brand

AP-1500 ETCHING PRIMER



PRODUCT DESCRIPTION

Armour Proof AP-1500 Etching Primer is a solvent-based primer designed to maximize adhesion to surfaces that can be difficult to adhere to, such as TPO, PVC, Hypalon, Metal and a variety of other substrates. It is a fast-drying primer that provides strong adhesion on weathered and un-weathered surfaces. **AP-1500** is intended for use over a cleaned roof surface; contaminants such as dirt and debris prevent proper adhesion. **AP-1500** is intended to be used in conjunction with an approved Armour Proof Coating product.

APPLICATION

Apply **AP-1500** until roof appears to be a consistent charcoal color. Apply at a rate of 330 square feet per gallon (0.33 gallons per square). Additional material may be required for porous substrates. Apply primer with small airless sprayer or a medium nap roller. Over-application or use of multiple coats can reduce adhesion performance. **AP-1500** should be top coated within 7 days.

PREPARATION OF SUBSTRATE

Surface must be pressure washed clean, free of all loose particles, dirt debris and other contaminants that could inhibit adhesion. Refer to the Armour Proof Coatings Specification for detailed instructions on how to prepare the specific substrate.

CLEANUP

Soap and water can be used to clean tools before this product dries. Dried material may be cleaned up with mineral spirits or waterless hand cleaner. Use care when handling solvents.

LIMITATIONS AND PRECAUTIONS

AP-1500 should not be applied when it is raining or when the threat of rain is imminent. AP-1500 should be applied in only one coat. This product contains flammable solvents and is intended for use by professional contractors only. Adhesion tests should always be performed to ensure suitability of use.

WARRANTY

This product will perform as claimed if directions are followed. Armour Proof Coatings cannot control conditions of application and substrate, or methods used. This warranty is limited to replacement of the defective material used, and does not include labor or labor costs.



TOOLS NEEDED ▾



PACKAGING SIZES ▾

