



Del-Val 213 Elastomeric Cement (Trowel Grade)

Description:

Del-Val 213 Elastomeric Cement contains a blend of SBS rubbers with solvent based asphalts and reinforcing fibers. Del-Val 213 Elastomeric Cement dries to a tough, durable, flexible coating that gives excellent performance over a wide range of temperatures and weather conditions

Uses:

Del-Val 213 Elastomeric Cement is designed for a use of flat roof surfaces with positive drainage. It may be used on a variety of surfaces including new or existing built up roofs, APP, SBS, smooth or granulated surfaces, metal surfaces and roll-roofing. DO NOT USE with TPO, EPDM, PVC or other single ply membranes.

Preparation:

Repair all holes, cracks, blisters, tears or breaks by spreading 213 Elastomeric Cement (Trowel Grade) over damaged area then embed United Asphalt Cotton, Fiberglass or Polyester Fabric.

Application:

Apply with a trowel or putty knife. Spread Del-Val 213 Elastomeric Cement to approximately 1/8" thickness and work thoroughly into the problem area.

Coverage:

Asphalt Surfaces: apply at the rate of approximately 3-4 gallons per 100 sq. ft.

Cleanup:

Clean tools with mineral spirits, taking necessary precautions when handling combustible liquids.

Code Approvals/Compliance:

This product meets or exceeds the requirements of ASTM 4586 Type 1

Precaution:

DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F



Tools needed:



Available in the following sizes:

