

Revision Date: 05.02.18

Del-Val

DELIVERING VALUE

DEL-VAL 100 QUICK-DRY ASPHALT PRIMER

Description

Del-Val 100 Quick-Dry Asphalt Primer is a general purpose penetrating asphalt primer that is used to help adhesion in all types of surfaces prior to the application of hot or cold asphalt coatings.

Uses

Del-Val 100 Quick-Dry Asphalt Primer is designed for use as an all-purpose utility prime coat for concrete, masonry, Gypsum, brick and metal surfaces, where roofing, waterproofing, damproofing and other asphalt coatings are applied DO NOT USE with TPO, EPDM, PVC or other single-ply membranes.

Preparation

All surfaces must be clean and dry and free of any oil, grease, dirt and all other foreign matter.

Application

Apply to a clean dry surface using a brush, roller or heavy duty spray equipment. For best results weather should be clear with no threat of rain for 24 hours. Drying time varies with weather conditions.

Coverage

Apply at a rate of approximately 1 gallon per 100 sq. ft. depending upon absorbency and type of surface that is being primed.

Cleanup

Clean tools with mineral spirits, taking necessary precautions when handling combustible liquids.


Code Approvals/Compliance

This product meets or exceeds the requirements of ASTM D41 and Federal Spec SS-A-701B

LEARN MORE  UnitedAsphalt.com/DV100



TOOLS NEEDED



PACKAGING SIZES

