

Revision Date: 05.02.18

Del-Val

DELIVERING VALUE

DEL-VAL 110 FIBERED ROOF COATING

Description

Del-Val 110 Fibrated Roof Coating is a fiber reinforced asphalt roof coating that provides a durable watertight barrier over existing roof surfaces

Uses

Del-Val 110 Fibrated Roof Coating may be used on smooth surface BUR, or SBS and APP bituminous membranes, metal surfaces, roll-roofing. DO NOT USE with TPO, EPDM, PVC or other single ply membranes.

Preparation

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Repair all holes, cracks, blisters, tears or breaks by spreading Del-Val 211 Flashing Cement over damaged area then embed United Asphalt Cotton or Fiberglass fabric.

Application

Apply to a clean dry surface using a brush or squeegee. For best results weather should be clear with no threat of rain for 48 hours.

Coverage

Apply at the rate of approximately 4 gallons per 100 sq. ft. Must stir coating before using.

Cleanup

Clean tools with mineral spirits, taking necessary precautions when handling combustible liquids.


Code Approvals/Compliance

This product meets or exceeds the requirements of ASTM D 4479 Type I

LEARN MORE  UnitedAsphalt.com/DV110



TOOLS NEEDED



PACKAGING SIZES

