

Revision Date: 05.02.18

Del-Val

DELIVERING VALUE

DEL-VAL 305 SBS MODIFIED ALUMINUM ROOF COATING

Description

Del-Val 305 SBS Modified Aluminum Roof Coating is a highly rubberized aluminum roof coating. Formulated using selected asphalts and blended with high quality aluminum pigments, refined solvents and SBS rubber. Del-Val 305 SBS Modified Aluminum Roof Coating provides outstanding expansion and contraction along with excellent reflectance. When the product is applied, it dries to a flexible rubber-like film that protects the roof's surface from destructive UV rays and reduces roof temperatures.

Uses

Del-Val 305 is formulated for applications over metal roofs, new or existing built-up roofs, APP, SBS, smooth or granulated surfaces and mobile home roofs.

Preparation

Prepare the roof surface by sweeping clean any dust, dirt or debris. Use a wire brush to remove rust from metal. Roof surface must be oil-free and free of moisture both on and beneath the surface. Repair all leaks and problem areas.

Application

Apply with a soft bristled brush, paint roller or heavy-duty spray equipment. Product should be mechanically mixed for several minutes before applying. Spread the product uniformly over the roof surface.

Coverage

Apply at the rate of 1.5 to 2 gallons per 100 sq. ft. Coverage may vary on different roof surfaces.

Cleanup


Clean tools with mineral spirits, taking necessary precautions when handling combustible liquids.

Precaution

DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F. DO NOT APPLY IF THERE IS A THREAT OF RAIN OR DEW WITHIN 24 HOURS. Applying Del-Val 305 directly over hot applied asphalt can result in alligating. Allow roof to cure thoroughly before coating.



TOOLS NEEDED ✓



PACKAGING SIZES ✓



V.O.C. Less than 500 g/L

Code Approvals/ Compliance:

Cool Roof Rated [PENDING]

LEARN MORE → UnitedAsphalt.com/DV305