

Revision Date: 03.19.20

# Del-Val

DELIVERING VALUE

## DEL-VAL 100 QUICK-DRY ASPHALT PRIMER

### Description

Del-Val 100 Quick-Dry Asphalt Primer is a general purpose penetrating asphalt primer that is used to help adhesion in all types of surfaces prior to the application of hot or cold asphalt coatings.

### Uses

Del-Val 100 Quick-Dry Asphalt Primer is designed for use as an all-purpose utility prime coat for concrete, masonry, Gypsum, brick and metal surfaces, where roofing, waterproofing, damproofing and other asphalt coatings are applied. **DO NOT USE with TPO, EPDM, PVC or other single-ply membranes.**

### Preparation

All surfaces must be clean and dry and free of any oil, grease, dirt and all other foreign matter.

### Application

Apply to a clean dry surface using a brush, roller or heavy duty spray equipment. For best results weather should be clear with no threat of rain for 24 hours. Drying time varies with weather conditions.

### Coverage

Apply at a rate of approximately 1 gallon per 100 sq. ft. depending upon absorbency and type of surface that is being primed.

### Cleanup

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.


### Code Approvals/Compliance

This product meets or exceeds the requirements of ASTM D41 and Federal Spec SS-A-701B

**LEARN MORE**  [UnitedAsphalt.com/DV100](http://UnitedAsphalt.com/DV100)



### TOOLS NEEDED



### PACKAGING SIZES

