

Revision Date: 03.19.20

Del-Val

DELIVERING VALUE

DEL-VAL 110 FIBERED ROOF COATING

Description

Del-Val 110 Fibered Roof Coating is a fiber reinforced asphalt roof coating that provides a durable watertight barrier over existing roof surfaces

Uses

Del-Val 110 Fibered Roof Coating may be used on smooth surface BUR, or SBS and APP bituminous membranes, metal surfaces, roll-roofing. **DO NOT USE with TPO, EPDM, PVC or other single-ply membranes.**

Preparation

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Repair all holes, cracks, blisters, tears or breaks by spreading Del-Val 211 Flashing Cement over damaged area then embed United Asphalt Cotton or Fiberglass fabric.

Application

Apply to a clean dry surface using a brush or squeegee. For best results weather should be clear with no threat of rain for 48 hours.

Coverage

Apply at the rate of approximately 4 gallons per 100 sq. ft. Must stir coating before using.

Cleanup

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.


Code Approvals/Compliance

This product meets or exceeds the requirements of ASTM D 4479 Type I

LEARN MORE  UnitedAsphalt.com/DV110



TOOLS NEEDED



PACKAGING SIZES

