

Revision Date: 03.19.20

Del-Val

DELIVERING VALUE

DEL-VAL 212 SBS MODIFIED FLASHING CEMENT – TROWEL GRADE

Description

Del-Val 212 SBS Modified Flashing Cement is a high quality cement that is formulated to a heavy smooth trowel consistency with great elasticity. This product is used as a cold applied flashing cement in many type of asphalt roof membranes. Del-Val 212 SBS Modified Flashing Cement is ideal for attaching roofing membranes to steep slope and parapet walls.

Uses

This product is primary used for applying SBS modified bitumen membrane flashings to parapet walls, curbs and repairing roof penetrations. Used for sealing laps on SBS modified roofs and also to seal penetrations on APP products. Great for repairing (asphalt shingles, built-up roofs, metal joints, masonry surfaces, chimneys, vents, skylights and gutters). **DO NOT USE with EPDM, PVC, TPO or other single-ply membranes.**

Preparation

Surface must be clean and free of dirt, dust, oil or grease and be free of any other foreign matter that would interfere with good adhesion. In colder climates we recommend storing the product at room temperature for 24 hours prior to application.

Application

Apply with a trowel or putty knife. Spread Del-Val 212 SBS Flashing Cement to approximately 1/8" thickness and work thoroughly into the problem area. Repairing cracks and blisters: if the area is 1/4" wide to 2" long apply United Asphalt Cotton or Fiberglass Fabric for reinforcement then cover with additional cement.

Coverage

Approximately 8 gallons per 100 sq. ft. (per coat)

Cleanup

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.


Code Approvals/Compliance

This product meets or exceeds the requirements of ASTM 4586 Type I

LEARN MORE  UnitedAsphalt.com/DV212



TOOLS NEEDED



PACKAGING SIZES

