

Revision Date: 03.19.20

# Del-Val

DELIVERING VALUE

## DEL-VAL 213 ELASTOMERIC SEALANT - BRUSH GRADE

### Description

Del-Val 213 Elastomeric Sealant (Brush Grade) contains a blend of SBS rubbers with solvent based asphalts and reinforcing fibers which forms an elastomeric coating. Del-Val 213 Elastomeric Sealant (Brush Grade) dries to a tough, durable, flexible coating that gives excellent performance over a wide range of temperatures and weather conditions.

### Uses

Del-Val 213 (Brush Grade) is designed for use on flat roof surfaces with positive drainage. It may be used on a variety of surfaces including new or existing built-up roofs, APP, SBS, smooth or granulated surfaces, metal surfaces and roll-roofing. **DO NOT USE with TPO, EPDM, PVC or other single-ply membranes.**

### Preparation

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Repair all holes, cracks, blisters, tears or breaks by spreading Del-Val 213 Elastomeric Sealant (Trowel Grade) over damaged area then embed United Asphalt Cotton, Fiberglass or Polyester Fabric. **Must mechanically mix coating before using.**

### Application

Apply to a clean dry surface using a brush, roller or squeegee. For best results weather should be clear with no threat of rain for 48 hours.

### Coverage

**Metal Surfaces:** Apply at the rate of approximately 1 gallon per 100 sq. ft.

**Asphalt Surfaces:** Apply at the rate of approximately 2-4 gallons per 100 sq. ft.

### Cleanup

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.

### Code Approvals/Compliance

This product meets or exceeds the requirements of ASTM D-4479 Type I

### Specifications

**Percent Elongation:** 914.70%


**Water Vapor Permeance:** 0.156 perms ASTM E96

**Water Absorption:** 0.12% D570-98

**Hardness, Shore A:** 41 ASTM D2240



### TOOLS NEEDED ✓



### PACKAGING SIZES ✓



### Precaution

DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F

**LEARN MORE** → [UnitedAsphalt.com/DV213BG](http://UnitedAsphalt.com/DV213BG)