

Revision Date: 03.19.20

# Del-Val

DELIVERING VALUE

## DEL-VAL 400 NON-FIBERED FOUNDATION COATING

### Description

Del-Val 400 Non-Fibered Foundation Coating is a non-fibrated asphalt coating that is used to prevent moisture penetration through foundation wall surfaces. After the product is applied it forms a smooth, flexible shell that helps resist the entrance of moisture through foundation walls.

### Uses

Del-Val 400 Non-Fibered Foundation Coating is used for exterior below-grade masonry and block walls where no hydrostatic pressure is present.

### Preparation

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Must stir coating before using.

### Application

Can be applied using: brush, roller, or heavy duty spray equipment. Allow 24 hours drying time before backfilling against the foundation walls. Do not apply over wet/damp or frost covered surfaces.

### Coverage

**Masonry Surfaces:** apply at the rate of approximately 1 to 1.5 gallons per 100 sq. ft.

### Cleanup

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.


### Precaution

DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F

**LEARN MORE**  [UnitedAsphalt.com/DV400](http://UnitedAsphalt.com/DV400)



### TOOLS NEEDED



### PACKAGING SIZES

